

Product Description		
Specification	Specification Link	Specification Link
Brochure	Brochure Link	Brochure Link
Warranty		
Finish/Rust Through	10 Year	10 Year
Delamination	10 Year	10 Year
Material & Workmanship	1 Year	1 Year
Hardware	1 Year	1 Year, Optional 8 Year
Physical Properties		
Section Thickness	1-5/8"	1 3/4"
Exterior Gauge	27 Gauge	27 Gauge
Exterior Profile	Ribbed	Minor Ribbed
Exterior Emboss	Textured	Stucco
Interior Gauge/Back Cover	27 Gauge	27 Gauge
Thermal Break	Yes	Yes
Meeting Rail	Shiplap	Tongue & Groove
End Stile	16 Gauge	18 Gauge Minimum Single; 16 Gauge Minimum
Components		
Insulation	Polyurethane	Intellicore® (Polyurethane)
Glazing Frames	24"x12", 24"x7", Aluminum Full View	Aluminum Full Vision,24"x12",24"x8",26"x13"
Glazing Thickness	1/8", 1/4", 1/2", 5/8"	1/8", 1/4", 1/2", 5/8"
Glazing Type	Insulated, Tempered, Polycarbonate, Multi-Wall Polycarbonate	Acrylic, Insulated, Insulated Tempered, Tempered, Lexan
Standard Finishes	White, Tan, Gray, Industrial Brown	White, Glacier White, Brown, Mocha Brown, Commercial Tan, Charcoal, Gray
Premium Finish	Not Published	ColorBlast® 2-Part Polane (Sherwin Williams), Trinar White, Trinar Beige
Track Configurations	2", 3" LHR, Vertical, HL, FRP, Standard	2", 3" LHR, Vertical, HL, FRP, Standard, Tapered
Counterbalance	100k, 50k, 25k, 10k	100k, 50k, 25k, 10k
Lock	Slide Lock(s)	Slide Lock(s), Keyed Lock
Performance		
UFactor	Not Published	0.18 Btu/hr-ft ² -Fo
R Value	14.86	16.2
Air Infiltration	0.08 cfm/ft ²	0.25 cfm/ft ² at 25 mph
STC Rating	Not Published	23
Flamespread	Not Published	Class II (or B) 40 FSR
Smoke Developed Index	Not Published	400 SDI

All product information on this page is based on publications and materials provided by each product's respective manufacturer publicly available as of July 1, 2020.

Clopay Corporation 8585 Duke Boulevard Mason OH 45040